



## ZPMV2.E308613 Wiring, Printed - Component

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

## Wiring, Printed - Component

[See General Information for Wiring, Printed - Component](#)

**HIGH-TECH ELETTRONICA**

E308613

VIALE COLLI 63

10098 RIVOLI, TO ITALY

	Cond Width		Cond	SS/ DS/ DSO	Max Area Diam mm(in)	Solder		Max Oper Temp C		Meets UL796 DSR	C T I
	Min	Edge				Thk mic(mil)	Limits C	sec	Flame Class		
Type	mm(in)	mm(in)	mic(mil)	DSO	mm(in)	C	sec	C	Class	DSR	I
<b>Multilayer printed wiring boards.</b>											
<b>2A</b>	0.2 (0.008)	0.25 (0.010)	16.5 (0.65)	DS	25.4 (1.0)	260	10	105	V-0	All	3
<b>3M</b>	0.075 (0.003)	0.10 (0.004)	17 (0.67) Int:68	DS	50.8 (2.0)	288	10	130	V-0	All	*
<b>3M1</b>	0.10 (0.004)	0.10 (0.004)	17 (0.67) Int:68	DS	25.4 (1.0)	260	10	120	V-0	All	*
<b>3M2</b>	0.10 (0.004)	0.10 (0.004)	17 (0.67) Int:68	DS	25.4 (1.0)	288	10	130	V-0	All	*
<b>Multilayer printed wiring boards made from prefabricated (mass-laminated).</b>											
<b>2</b>	0.15 (0.006)	0.15 (0.006)	16.5 (0.65)	DS	50.8 (2.0)	260	10	120	V-0	All	2
<b>Multilayer printed wiring boards, flammability only Recognition.</b>											
<b>3M3</b>	-	-	-	DS	-	288	10	-	V-0	-	-
<b>Multilayer rigid flex composite, flexible materials interconnect constructions, flammability only Recognition.</b>											
<b>3RF</b>	-	-	-	-	-	280	10	-	V-0	-	-
<b>Single layer printed wiring boards.</b>											
<b>1</b>	0.43 (0.017)	0.58 (0.023)	33 (1.30)	DS	12.7 (0.5)	260	10	100	V-0	All	-
<b>1A</b>	0.15 (0.006)	0.15 (0.006)	16.5 (0.65)	DS	50.8 (2.0)	260	10	120	V-0	All	1
<b>1B</b>	0.2 (0.008)	0.25 (0.010)	16.5 (0.65)	DS	25.4 (1.0)	260	10	105	V-0	All	*
<b>3D</b>	0.075 (0.003)	0.10 (0.004)	17 (0.67)	DS	50.8 (2.0)	288	10	130	V-0	All	*
<b>3D1</b>	0.10 (0.004)	0.10 (0.004)	17 (0.67)	DS	50.8 (2.0)	260	10	120	V-0	All	*
<b>3D2</b>	0.10 (0.004)	0.10 (0.004)	17 (0.67)	DS	50.8 (2.0)	288	10	130	V-0	All	*

NOTE - A triangle is marked on those products within a given type designation that comply with direct support of current-carrying parts performance level requirements of UL 796. "All" is used to indicate that all base materials under that type designation comply with direct support of current-carrying parts performance level requirement of UL796.

\* - CTI PLC is marked on individual board.



Marking: Company name or trademark or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2014-05-20